

DRYFORCETM WATERPROOF 60L DUFFEL

WARNING This indication alerts you to the fact that ignoring the contents described herein can result in potential serious injury or death if not followed.

CAUTION This indication alerts you to the fact that ignoring the contents described herein can or will result in material damage and/or personal injury.

ATTENTION This indication alerts you to the fact if you ignore this detail you will affect the performance or functionality of the product.

All Ciro products are designed for "easy assembly" and/or "plug and play". We recommend a competent mechanic install our products, using standard mechanical procedures to assure a safe and successful installation. Read completely and understand the instructions prior to starting installation.

NOTE: Ciro products are designed and manufactured under very strict quality control. Ciro warrants that products sold to the original purchaser shall be free from any defects in materials and workmanship for a period of 3 (three) years from the date of purchase, and a lifetime warranty against LED failure. Ciro will have no obligation if the customer cannot show proof of purchase. Warranty will not be granted unless the part is properly installed and maintained. Ciro will not be liable for any consequential and incidental damages, including labor, or non-Ciro products. Please visit Ciro3d.com for our complete warranty policy.

CAUTION

Ciro is not responsible for improper loads or unsafe positioning of the Dryforce 60L duffel bag. Be sure the weight of the contents placed in the bag do not exceed safe limits. It is the users responsibility to determine what the safe limit is based on the position of the bag, proper securing of the bag and the weight limits given for the motorcycle by its manufacturer.

WARNING

It is the end user's responsibility to use good judgment. Follow the included mounting suggestions. Chose additional tie down straps that work for your application. Adhere to the vehicle manufacturer's GAWR and GVWR (gross axle weight rating and gross vehicle weight rating). When attaching luggage to a vehicle. Added weight, shifting loads, and improperly attached luggage can result in loss of control and can lead to death or serious injury.

WARNING

Prevent potential serious injury. Ensure the bag is fastened and straps are secure before riding the motorcycle.

Mounting Suggestions:

- 1. Park on a level surface, allow the vehicle to cool.
- The included Tie down / Shoulder strap is designed to be used as an adjustable tie down strap. Use additional straps to secure the bag in a manor appropriate for your application. FIG.1
- When installing the 60L Duffel Bag onto a H-D Tour Pack Luggage Rack use the safety straps on the ends of the bag to secure the bag to the rack. Use additional straps to secure the bag in a manor appropriate for your application. FIG.2
- 4. Use the D-rings on the side of the bag to attach straps to secure the bag to appropriate mounting locations. Do not secure mounting straps to moving components such as the swingarm. Secure straps to stationary locations only. FIG.1,3
- 5. Pre-load the straps by applying light downward force while the straps are tightened.

Items Included:

- 60L Duffel
 Tie down / shoulder strap
- <image>







ATTENTION

Verify that the bag is securely attached before operating the motorcycle. Secure all straps away from painted surfaces, moving parts, pinch points or heat. Check the straps before each ride and at each stop. Bag contents may shift during operation which can result in loose straps. Roll up any excess length in all of the straps and secure it.

