



INSTALLATION

HANDLEBAR CONTROL DRESS-UP KIT 1741

FITS: '04-UP SPORTSTER MODELS

PARTS INCLUDED

- 1 XL Clutch Perch
- 2 XL Handle Bar Clamp
- 1 XL Master Cylinder Cover
- 1 Hardware Kit including:
 - 4 M6x1x20 Socket Head Cap Screws
 - 2 M4x.7x25mm Button Head Cap Screw
 - 2 M5x.08x12mm Button Head Cap Screw
 - 1 XL Master Cylinder Bracket
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Hex Wrenches, Snap Ring Pliers and Combination Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE

BRAKE SIDE

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

CAUTION! Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

STEP 2 Remove the mirror from the master cylinder assembly.

STEP 3 While holding the master cylinder assembly in place, remove the master cylinder handlebar clamp. Replace it with one of the chrome clamp halves and M6x1x20 Socket Head Cap Screws. Tighten this clamp so the master cylinder is in its original position.

CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.

kuryakyn.com



STEP 4 Turn the handlebars so the master cylinder reservoir is in its most level position. Remove the two Phillips screws that hold the reservoir top cover in position. (This is a good time to check your brake fluid level.) Place the supplied Master Cylinder Bracket (PIC 1) on top of the reservoir top cover and secure it with the M4x.7x25mm Button Head Cap Screws. Tighten evenly and securely, but do not over tighten. Set the cover in place over the master cylinder reservoir. Secure in position with the two M5x.08x12mm Button Head Cap Screws (PIC 2). Replace the mirror.

PIC. 1




CLUTCH SIDE

STEP 1 Slide the rubber “bellows” that covers the clutch cable adjuster, out of the way. Loosen and shorten the adjuster all the way to give maximum slack in the cable.

CAUTION! Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

STEP 2 Remove the mirror from the clutch perch. Using a small external snap ring pliers, remove the circlip from the pivot pin. Remove the clutch lever pivot pin from the stock clutch perch.

PIC. 2



STEP 3 Pull the cable housing out away from the perch. Swing the cable outward, away from the handlebar. Pull the cable/lever assembly away so it is completely free of the perch, you may let the lever hang from the cable.

STEP 4 Remove the stock perch and clamp from the handlebar. Replace them with the new XL Clutch Perch and clamp. Secure them with two of the supplied M6x1x20 Socket Head Cap Screws. Tighten securely.

STEP 5 Apply grease to all pivot points (this is also a good time to lube your clutch cable) and reassemble all components in the reverse order of disassembly.

STEP 6 Once all components are reassembled, adjust your clutch cable. We suggest referring to your factory service manual for this procedure. Be sure to leave 1/8” of free play where the cable housing meets the clutch perch. Be careful not to over tighten the clutch cable adjuster, as it can be broken! Spray cable lube down on the cable adjuster and slide the rubber bellows back into place.

PIC. 3



WARNING! FAILURE TO ADJUST THE CLUTCH CABLE PROPERLY MAY RESULT IN LOSS OF CONTROL CAUSING SEVERE INJURY OR DEATH.

STEP 7 Tighten all fasteners.

ATTENTION! It is the installer’s responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.

Ride On!